

SURFACE CARE & FUNCTIONAL WAX · LOW-MOISTURE WOOD CARE + HCHO
BARRIER

Formaldehyde Removal Care Wax

2-in-1 wood conditioning wax and formaldehyde scavenging barrier for moisture-sensitive veneers, solid timber, and finished furniture.

PATHWAY

Wax Emulsion + HCHO Cross-Linker



TECHNICAL SPECIFICATIONS & OPERATING PARAMETERS

Factory QC Standard · Verified Batch Parameters

Physical Form	Smooth milky-white conditioning emulsion / liquid wax
Active Components	Refined plant & carnauba wax emulsion, active aldehyde scavenger
Recommended Dosage	10 – 15 g/m ² wiped evenly with microfiber cloth
Applicable Surfaces	Finished wood furniture, veneered panels, laminated cabinets, wood floors
Packaging Options	500g / 1kg bottles, 5kg / 20kg B2B pails
Product Grade	Fine Millwork, Veneer & Luxury Leather Preservation Grade
Specific Gravity / Density	0.94 - 0.98 g/cm ³ (20 °C)
Flash Point & VOC Content	> 95 °C (Closed cup, non-regulated) · VOC: < 15 g/L (Zero aromatic solvents)
Application Method	Microfiber applicator pad wipe-on and dry buffing
Transport & Customs HS Code	Non-Dangerous Goods (Non-DG for Sea/Air) · HS 3405.20.0000
Quality & Test Compliance	EN 717-1 Chamber Flux & ISO 2409 Surface Gloss Retention (88.5% surface HCHO flux reduction with zero wood grain swelling)